

REPORT NUMBER: ITL85760

ISSUE DATE: 10/23/15

PAGE: 1 OF 9

PREPARED FOR: LED ROADWAY LIGHTING LTD.

CATALOG NUMBER: NXT 48M 0 X 2ES 6 XX 3 XX X XX X

LUMINAIRE: CAST METAL HOUSING WITH SEMI-DIFFUSE INTERIOR FINISH, 2 WHITE CIRCUIT BOARDS EACH WITH 36 LEDS, 2 CLEAR PLASTIC LENSES WITH 1 OPTIC PER LED, CLEAR FLAT GLASS LENS IN CAST SEMI-DIFFUSE METAL DOOR FRAME. ONLY 48 LEDS ON FOR THIS TEST.

LAMPS: FORTY-EIGHT WHITE LIGHT EMITTING DIODES (LEDs), VERTICAL BASE-UP POSITION.

INPUT ELECTRICAL: 120.0 VOLTS, 89.4 WATTS, 0.755 AMPS

LED DRIVER: LED ROADWAY LIGHTING J100UN, DRIVER HAS MULTIPLE LEADS, ONLY LINE INPUT AND LED OUTPUT LEADS CONNECTED FOR THIS TEST, OUTPUT CURRENT ROTARY SWITCH SET TO 600mA. LRL65633-LF SURGE PROTECTOR.

NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED AT RATED INPUT VOLTAGE (120VAC, 60Hz) TO THE DRIVER AND SURGE PROTECTOR. SURGE PROTECTOR INFORMATION PROVIDED BY CLIENT.

TEST PROCEDURE: IESNA LM-79-08

TEST DISTANCE = 35.0 FEET

TOTAL LUMEN OUTPUT: 10200

COLOR TEMPERATURE AS MEASURED IN INTEGRATING SPHERE TEST # ITL85775: 3764K

COLOR RENDERING INDEX AS MEASURED IN INTEGRATING SPHERE TEST # ITL85775: 73

LED DC DRIVE CURRENT (mA): 600 (PROVIDED BY CLIENT)


POWER FACTOR: 98.7 %

BUG RATING: B2 U0 G2

LUMINAIRE EFFICACY: 114.1 lm/W

IES CLASSIFICATION: Medium, Type II

**CUTOFF DESIGNATION IS NOT INTENDED TO BE USED WITH ABSOLUTE PHOTOMETRIC TESTS.



FLUX DISTRIBUTION

LUMENS	DOWNWARD	UPWARD	TOTALS
HOUSE SIDE	3323	0	3323
STREET SIDE	6877	0	6877
TOTALS	10200	0	10200

TESTING WAS PERFORMED IN ACCORDANCE WITH IESNA LM-79-08
TEST ANGULAR INCREMENTS AND REPORT FORMATTING WAS BASED ON IESNA LM-31-95

THIS REPORT IS BASED ON PUBLISHED INDUSTRY PROCEDURES. FIELD PERFORMANCE MAY DIFFER FROM LABORATORY PERFORMANCE.



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

PHONE: (303) 442-1255

FAX: (970) 535-3114

E-MAIL: itl@itlboulder.com

WEBSITE: www.itlboulder.com


NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.

4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINATION

Values based on 30 foot mounting height.



REPORT NUMBER: ITL85760

ISSUE DATE: 10/23/15

PAGE: 2 OF 9

PREPARED FOR: LED ROADWAY LIGHTING LTD.

CATALOG NUMBER: NXT 48M 0 X 2ES 6 XX 3 XX X XX X

LUMINAIRE: CAST METAL HOUSING WITH SEMI-DIFFUSE INTERIOR FINISH, 2 WHITE CIRCUIT BOARDS EACH WITH 36 LEDS, 2 CLEAR PLASTIC LENSES WITH 1 OPTIC PER LED, CLEAR FLAT GLASS LENS IN CAST SEMI-DIFFUSE METAL DOOR FRAME. ONLY 48 LEDS ON FOR THIS TEST.

LAMPS: FORTY-EIGHT WHITE LIGHT EMITTING DIODES (LEDS), VERTICAL BASE-UP POSITION.

INPUT ELECTRICAL: 120.0 VOLTS, 89.4 WATTS, 0.755 AMPS

LED DRIVER: LED ROADWAY LIGHTING J100UN, DRIVER HAS MULTIPLE LEADS, ONLY LINE INPUT AND LED OUTPUT LEADS CONNECTED FOR THIS TEST, OUTPUT CURRENT ROTARY SWITCH SET TO 600mA. LRL65633-LF SURGE PROTECTOR.

NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED AT RATED INPUT VOLTAGE (120VAC, 60Hz) TO THE DRIVER AND SURGE PROTECTOR. SURGE PROTECTOR INFORMATION PROVIDED BY CLIENT.

TEST PROCEDURE: IESNA LM-79-08

TEST DISTANCE = 35.0 FEET


IES Classification: Medium, Type II


--- 1/2 Maximum Candela trace

X Maximum Candela point

Checked *B. HYRE*

Approved *R. BEATTIE*
Lighting Engineer





itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85760

ISSUE DATE: 10/23/15

PAGE: 3 OF 9

PREPARED FOR: LED ROADWAY LIGHTING LTD.

CATALOG NUMBER: NXT 48M 0 X 2ES 6 XX 3

XX X XX X

LUMINAIRE: CAST METAL HOUSING WITH SEMI-DIFFUSE INTERIOR FINISH, 2 WHITE CIRCUIT BOARDS EACH WITH 36 LEDS, 2 CLEAR PLASTIC LENSES WITH 1 OPTIC PER LED, CLEAR FLAT GLASS LENS IN CAST SEMI-DIFFUSE METAL DOOR FRAME. ONLY 48 LEDS ON FOR THIS TEST.

LAMPS: FORTY-EIGHT WHITE LIGHT EMITTING DIODES (LEDs), VERTICAL BASE-UP POSITION.

INPUT ELECTRICAL: 120.0 VOLTS, 89.4 WATTS, 0.755 AMPS


LED DRIVER: LED ROADWAY LIGHTING J100UN, DRIVER HAS MULTIPLE LEADS, ONLY LINE INPUT AND LED OUTPUT LEADS CONNECTED FOR THIS TEST, OUTPUT CURRENT ROTARY SWITCH SET TO 600mA. LRL65633-LF SURGE PROTECTOR.

NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED AT RATED INPUT VOLTAGE (120VAC, 60Hz) TO THE DRIVER AND SURGE PROTECTOR. SURGE PROTECTOR INFORMATION PROVIDED BY CLIENT.

TEST PROCEDURE: IESNA LM-79-08

TEST DISTANCE = 35.0 FEET

MAXIMUM PLANE AND MAXIMUM CONE PLOTS OF CANDELA






REPORT NUMBER: ITL85760
ISSUE DATE: 10/23/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 4 OF 9

COEFFICIENTS OF UTILIZATION AND FLUX DISTRIBUTION



	LUMENS	PERCENT OF FIXTURE
DOWNWARD STREET SIDE	6877	67.4
DOWNWARD HOUSE SIDE	3323	32.6
DOWNWARD TOTAL	10200	100.0
UPWARD STREET SIDE	0	0.0
UPWARD HOUSE SIDE	0	0.0
UPWARD TOTAL	0	0.0
TOTAL FLUX	10200	100.0

EFFICACY = 114.1 lm/W

ALL CANDELA AND LUMENS IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY.
THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE
LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.



PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

REPORT NUMBER: ITL85760
ISSUE DATE: 10/23/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 5 OF 9

FLUX DISTRIBUTION BY SOLID ANGLE

(PER IESNA TM-15-11, LUMINAIRE CLASSIFICATION
SYSTEM FOR OUTDOOR LUMINAIRES)

	LUMENS	PERCENT OF FIXTURE	BUG ZONE RATINGS
FORWARD LIGHT	6877.	67.4	
FL (0- 30)	1235.9	12.1	
FM (30- 60)	3476.8	34.1	
FH (60- 80)	2106.7	20.7	G2
FVH(80- 90)	57.6	0.6	G1
BACK LIGHT	3323.	32.6	
BL (0- 30)	876.5	8.6	B2
BM (30- 60)	1622.5	15.9	B2
BH (60- 80)	792.4	7.8	B2 G2
BVH(80- 90)	31.3	0.3	G1
UPLIGHT	0.	0.0	
UL (90-100)	0.0	0.0	U0
UH (100-180)	0.0	0.0	U0
TRAPPED LIGHT	0.	0.0	
TOTAL FLUX	10200.	100.0	

BACKLIGHT, UPLIGHT, AND GLARE (BUG) RATINGS
(PER ADDENDUM A FOR IESNA TM-15-11)

BUG RATING: B2 U0 G2



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85760
ISSUE DATE: 10/23/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.


PAGE: 6 OF 9

CANDELA TABULATION

	STREET SIDE										
	0.0	5.0	15.0	25.0	35.0	45.0	55.0	65.0	71.5	75.0	85.0
180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
87.5	2.	2.	2.	1.	1.	1.	1.	3.	5.	6.	6.
85.0	14.	16.	20.	17.	12.	11.	9.	11.	15.	14.	15.
V 82.5	38.	42.	58.	50.	37.	44.	39.	77.	591.	567.	336.
E 80.0	77.	82.	111.	82.	72.	88.	85.	283.	1992.	2161.	1480.
R 77.5	115.	119.	146.	113.	119.	123.	153.	927.	3337.	3662.	2831.
T 75.0	138.	145.	170.	164.	165.	177.	280.	2459.	4663.	4952.	3818.
I 72.5	178.	188.	207.	217.	213.	278.	765.	4118.	5988.	6147.	4753.
C 70.0	240.	247.	259.	275.	267.	530.	1878.	5486.	6879.	6722.	5399.
A 69.0<<	264.	271.	281.	302.	298.	734.	2338.	5891.	7066.	6849.	5565.
L 67.5	300.	309.	318.	347.	397.	1183.	2974.	6045.	6861.	6747.	5654.
65.0	381.	397.	413.	523.	863.	2066.	3725.	5647.	5986.	5923.	5317.
A 62.5	593.	631.	693.	955.	1476.	2625.	3907.	5220.	5503.	5434.	4996.
N 60.0	951.	998.	1085.	1377.	1835.	2764.	3834.	4943.	5177.	5116.	4830.
G 57.5	1282.	1290.	1360.	1609.	2000.	2793.	3785.	4767.	4939.	4873.	4710.
L 55.0	1473.	1475.	1543.	1756.	2134.	2809.	3723.	4679.	4801.	4705.	4576.
E 52.5	1626.	1634.	1679.	1893.	2270.	2834.	3623.	4321.	4429.	4402.	4413.
50.0	1742.	1756.	1809.	2033.	2403.	2894.	3559.	4052.	4137.	4145.	4234.
47.5	1846.	1879.	1946.	2163.	2528.	2962.	3488.	3856.	3925.	3962.	4066.
45.0	1963.	1998.	2089.	2293.	2635.	3017.	3392.	3657.	3756.	3811.	3915.
42.5	2094.	2134.	2245.	2472.	2760.	3066.	3328.	3491.	3596.	3663.	3776.
40.0	2295.	2344.	2482.	2677.	2894.	3115.	3251.	3347.	3453.	3521.	3619.
37.5	2596.	2633.	2746.	2861.	3006.	3148.	3163.	3232.	3339.	3399.	3480.
35.0	2846.	2890.	2953.	3007.	3080.	3116.	3067.	3134.	3238.	3292.	3342.
30.0	3106.	3152.	3154.	3145.	3071.	2935.	2917.	3030.	3119.	3152.	3137.
25.0	3091.	3129.	3071.	2981.	2876.	2816.	2884.	2978.	3030.	3035.	2975.
20.0	2842.	2882.	2849.	2816.	2815.	2863.	2916.	2961.	2964.	2946.	2856.
15.0	2829.	2876.	2882.	2888.	2909.	2931.	2953.	2943.	2915.	2889.	2797.
10.0	2913.	2961.	2958.	2949.	2955.	2954.	2935.	2899.	2870.	2849.	2767.
5.0	2877.	2920.	2914.	2898.	2890.	2879.	2863.	2836.	2815.	2798.	2751.
0.0	2720.	2720.	2720.	2720.	2720.	2720.	2720.	2720.	2720.	2720.	2720.

||
PLANE OF MAXIMUM CANDELA

CONE OF MAXIMUM CANDELA



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85760
ISSUE DATE: 10/23/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 7 OF 9

CANDELA TABULATION

HOUSE SIDE		LATERAL ANGLE										
		90.0	95.0	105.0	115.0	125.0	135.0	145.0	155.0	165.0	175.0	180.0
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	7.	6.	4.	2.	1.	1.	1.	1.	0.	0.	0.
	85.0	15.	13.	11.	9.	8.	14.	20.	36.	29.	10.	2.
V	82.5	373.	237.	36.	38.	37.	58.	75.	90.	111.	110.	108.
E	80.0	1292.	955.	105.	84.	79.	112.	147.	170.	214.	224.	227.
R	77.5	2421.	1822.	231.	135.	127.	159.	208.	253.	331.	365.	363.
T	75.0	3353.	2642.	456.	195.	182.	202.	243.	263.	385.	429.	424.
I	72.5	4284.	3526.	856.	265.	228.	240.	274.	258.	356.	394.	392.
C	70.0	4884.	4069.	1327.	334.	267.	275.	311.	274.	317.	314.	308.
A	69.0<<	5025.	4177.	1492.	359.	282.	288.	326.	286.	314.	292.	287.
L	67.5	5092.	4229.	1722.	393.	307.	306.	346.	306.	320.	283.	280.
	65.0	4896.	4203.	2076.	454.	343.	338.	373.	348.	338.	299.	296.
A	62.5	4740.	4199.	2385.	547.	374.	376.	393.	395.	369.	330.	321.
N	60.0	4674.	4233.	2660.	714.	408.	411.	397.	424.	412.	369.	356.
G	57.5	4636.	4294.	2899.	966.	451.	446.	415.	440.	444.	407.	394.
L	55.0	4533.	4259.	3080.	1248.	507.	481.	440.	450.	468.	436.	421.
E	52.5	4369.	4097.	3065.	1543.	599.	514.	469.	474.	495.	458.	445.
	50.0	4209.	3980.	3087.	1803.	747.	547.	501.	503.	507.	481.	472.
	47.5	4043.	3866.	3095.	1996.	933.	588.	535.	529.	521.	499.	496.
	45.0	3884.	3747.	3071.	2123.	1124.	674.	571.	555.	542.	527.	526.
	42.5	3731.	3608.	3028.	2201.	1303.	802.	619.	581.	568.	556.	556.
	40.0	3573.	3463.	2966.	2252.	1456.	939.	708.	623.	596.	582.	581.
	37.5	3434.	3323.	2891.	2281.	1587.	1069.	820.	704.	648.	624.	623.
	35.0	3288.	3195.	2818.	2296.	1700.	1205.	929.	804.	741.	712.	711.
	30.0	3065.	2966.	2681.	2312.	1894.	1510.	1211.	1047.	950.	906.	909.
	25.0	2892.	2801.	2580.	2340.	2066.	1791.	1561.	1384.	1256.	1208.	1199.
	20.0	2779.	2705.	2542.	2383.	2216.	2045.	1884.	1751.	1652.	1608.	1605.
	15.0	2732.	2672.	2554.	2442.	2342.	2240.	2152.	2075.	2011.	1980.	1989.
	10.0	2721.	2677.	2594.	2525.	2459.	2403.	2359.	2320.	2287.	2271.	2291.
	5.0	2728.	2704.	2657.	2622.	2589.	2552.	2532.	2511.	2493.	2485.	2510.
	0.0	2720.	2720.	2720.	2720.	2720.	2720.	2720.	2720.	2720.	2720.	2720.

CONE OF MAXIMUM CANDELA



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85760
ISSUE DATE: 10/23/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 8 OF 9

5-DEGREE
ZONAL LUMEN SUMMARY

0- 5	65
5- 10	193
10- 15	312
15- 20	417
20- 25	514
25- 30	611
30- 35	700
35- 40	771
40- 45	828
45- 50	885
50- 55	940
55- 60	975
60- 65	956
65- 70	900
70- 75	681
75- 80	363
80- 85	86
85- 90	3
90- 95	0
95-100	0
100-105	0
105-110	0
110-115	0
115-120	0
120-125	0
125-130	0
130-135	0
135-140	0
140-145	0
145-150	0
150-155	0
155-160	0
160-165	0
165-170	0
170-175	0
175-180	0

10-DEGREE
ZONAL LUMEN SUMMARY

0- 10	258
0- 20	987
0- 30	2112
0- 40	3583
0- 50	5296
0- 60	7212
0- 70	9067
0- 80	10111
0- 90	10200
0-100	10200
0-110	10200
0-120	10200
0-130	10200
0-140	10200
0-150	10200
0-160	10200
0-170	10200
0-180	10200



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85760
ISSUE DATE: 10/23/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 9 OF 9

ADDRESS: 115 CHAIN LAKE DRIVE
SUITE 201
HALIFAX, NOVA SCOTIA, CANADA B3S 1B3

THIS ITL REPORT WITH THE USE OF THE NVLAP LOGO SHALL NOT BE USED BY
THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT
BY NVLAP, NIST, OR ANY AGENCY OF THE FEDERAL GOVERNMENT.