

REPORT NUMBER: ITL85360

ISSUE DATE: 08/12/15

PAGE: 1 OF 9

PREPARED FOR: LED ROADWAY LIGHTING LTD.

CATALOG NUMBER: NXT 36S 0 X 2ES 4 XX 3 XX X XX X

LUMINAIRE: CAST METAL HOUSING WITH GRAY PAINTED INTERIOR FINISH, 1 WHITE CIRCUIT BOARD WITH 36 LEDS, 1 CLEAR PLASTIC LENS WITH 1 OPTIC PER LED, CLEAR FLAT GLASS LENS IN CAST GRAY PAINTED METAL DOOR FRAME.

LAMPS: THIRTY-SIX WHITE LIGHT EMITTING DIODES (LEDs), VERTICAL BASE-UP POSITION.

INPUT ELECTRICAL: 120.0 VOLTS, 52.6 WATTS, 0.445 AMPS

LED DRIVER: LED ROADWAY LIGHTING J100UN, DRIVER HAS MULTIPLE LEADS, ONLY LINE INPUT AND LED OUTPUT LEADS CONNECTED FOR THIS TEST, OUTPUT CURRENT ROTARY SWITCH SET TO 450mA. LRL65633-LF SURGE PROTECTOR.

NOTE: DATA SHOWN IS ABSOLUTE FOR THE SAMPLE PROVIDED AT RATED INPUT VOLTAGE (120VAC, 60Hz) TO THE DRIVER AND SURGE PROTECTOR. SURGE PROTECTOR INFORMATION PROVIDED BY CLIENT.

TEST PROCEDURE: IESNA LM-79-08

TEST DISTANCE = 20.0 FEET

TOTAL LUMEN OUTPUT: 6072

COLOR TEMPERATURE AS MEASURED IN INTEGRATING SPHERE TEST # ITL85368: 3769K

COLOR RENDERING INDEX AS MEASURED IN INTEGRATING SPHERE TEST # ITL85368: 73

LED DC DRIVE CURRENT (mA): 450 (PROVIDED BY CLIENT)


POWER FACTOR: 98.5 %

BUG RATING: B2 U0 G1

LUMINAIRE EFFICACY: 115.4 lm/W

IES CLASSIFICATION: Medium, Type II

**CUTOFF DESIGNATION IS NOT INTENDED TO BE USED WITH ABSOLUTE PHOTOMETRIC TESTS.



FLUX DISTRIBUTION

LUMENS	DOWNWARD	UPWARD	TOTALS
HOUSE SIDE	2000	0	2000
STREET SIDE	4072	0	4072
TOTALS	6072	0	6072

TESTING WAS PERFORMED IN ACCORDANCE WITH IESNA LM-79-08
TEST ANGULAR INCREMENTS AND REPORT FORMATTING WAS BASED ON IESNA LM-31-95

THIS REPORT IS BASED ON PUBLISHED INDUSTRY PROCEDURES. FIELD PERFORMANCE MAY DIFFER FROM LABORATORY PERFORMANCE.



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

PHONE: (303) 442-1255

FAX: (970) 535-3114

E-MAIL: itl@itlboulder.com

WEBSITE: www.itlboulder.com


NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.

4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINATION

Values based on 30 foot mounting height.



REPORT NUMBER: ITL85360

ISSUE DATE: 08/12/15

PAGE: 2 OF 9

PREPARED FOR: LED ROADWAY LIGHTING LTD.

CATALOG NUMBER: NXT 36S 0 X 2ES 4 XX 3
XX X XX X

LUMINAIRE: CAST METAL HOUSING WITH GRAY
PAINTED INTERIOR FINISH, 1 WHITE
CIRCUIT BOARD WITH 36 LEDs, 1 CLEAR
PLASTIC LENS WITH 1 OPTIC PER LED,
CLEAR FLAT GLASS LENS IN CAST GRAY
PAINTED METAL DOOR FRAME.

LAMPS: THIRTY-SIX WHITE LIGHT EMITTING
DIODES (LEDs), VERTICAL BASE-UP POSITION.
INPUT ELECTRICAL: 120.0 VOLTS, 52.6

WATTS, 0.445 AMPS

LED DRIVER: LED ROADWAY LIGHTING J100UN,
DRIVER HAS MULTIPLE LEADS, ONLY LINE
INPUT AND LED OUTPUT LEADS CONNECTED
FOR THIS TEST, OUTPUT CURRENT ROTARY
SWITCH SET TO 450mA. LRL65633-LF SURGE
PROTECTOR.

NOTE: DATA SHOWN IS ABSOLUTE FOR THE
SAMPLE PROVIDED AT RATED INPUT VOLTAGE
(120VAC, 60Hz) TO THE DRIVER AND SURGE
PROTECTOR. SURGE PROTECTOR INFORMATION
PROVIDED BY CLIENT.

TEST PROCEDURE: IESNA LM-79-08

TEST DISTANCE = 20.0 FEET


IES Classification: Medium, Type II


--- 1/2 Maximum Candela trace

X Maximum Candela point

Checked *B. HYRE*

Approved *R. BEATTIE*
Lighting Engineer





itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85360

ISSUE DATE: 08/12/15

PAGE: 3 OF 9

PREPARED FOR: LED ROADWAY LIGHTING LTD.

CATALOG NUMBER: NXT 36S 0 X 2ES 4 XX 3

XX X XX X

LUMINAIRE: CAST METAL HOUSING WITH GRAY
PAINTED INTERIOR FINISH, 1 WHITE
CIRCUIT BOARD WITH 36 LEDS, 1 CLEAR
PLASTIC LENS WITH 1 OPTIC PER LED,
CLEAR FLAT GLASS LENS IN CAST GRAY
PAINTED METAL DOOR FRAME.

LAMPS: THIRTY-SIX WHITE LIGHT EMITTING
DIODES (LEDs), VERTICAL BASE-UP
POSITION.

INPUT ELECTRICAL: 120.0 VOLTS, 52.6
WATTS, 0.445 AMPS


LED DRIVER: LED ROADWAY LIGHTING J100UN,
DRIVER HAS MULTIPLE LEADS, ONLY LINE
INPUT AND LED OUTPUT LEADS CONNECTED
FOR THIS TEST, OUTPUT CURRENT ROTARY
SWITCH SET TO 450mA. LRL65633-LF SURGE
PROTECTOR.

NOTE: DATA SHOWN IS ABSOLUTE FOR THE
SAMPLE PROVIDED AT RATED INPUT VOLTAGE
(120VAC, 60Hz) TO THE DRIVER AND SURGE
PROTECTOR. SURGE PROTECTOR INFORMATION
PROVIDED BY CLIENT.

TEST PROCEDURE: IESNA LM-79-08

TEST DISTANCE = 20.0 FEET

MAXIMUM PLANE AND MAXIMUM CONE PLOTS OF CANDELA






REPORT NUMBER: ITL85360
ISSUE DATE: 08/12/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 4 OF 9

COEFFICIENTS OF UTILIZATION AND FLUX DISTRIBUTION



	LUMENS	PERCENT OF FIXTURE
DOWNWARD STREET SIDE	4072	67.1
DOWNWARD HOUSE SIDE	2000	32.9
DOWNWARD TOTAL	6072	100.0
UPWARD STREET SIDE	0	0.0
UPWARD HOUSE SIDE	0	0.0
UPWARD TOTAL	0	0.0
TOTAL FLUX	6072	100.0

EFFICACY = 115.4 lm/W

ALL CANDELA AND LUMENS IN THIS REPORT ARE BASED ON ABSOLUTE PHOTOMETRY.
THE COEFFICIENT OF UTILIZATION VALUES ARE BASED ON THE TOTAL ABSOLUTE
LUMEN OUTPUT OF THIS LUMINAIRE SAMPLE.



PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

REPORT NUMBER: ITL85360
ISSUE DATE: 08/12/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 5 OF 9

FLUX DISTRIBUTION BY SOLID ANGLE

(PER IESNA TM-15-11, LUMINAIRE CLASSIFICATION
SYSTEM FOR OUTDOOR LUMINAIRES)

	LUMENS	PERCENT OF FIXTURE	BUG ZONE RATINGS
FORWARD LIGHT	4072.	67.1	
FL (0- 30)	726.5	12.0	
FM (30- 60)	2050.8	33.8	
FH (60- 80)	1256.6	20.7	G1
FVH(80- 90)	37.8	0.6	G1
BACK LIGHT	2000.	32.9	
BL (0- 30)	523.5	8.6	B2
BM (30- 60)	977.9	16.1	B1
BH (60- 80)	478.7	7.9	B1 G1
BVH(80- 90)	19.8	0.3	G1
UPLIGHT	0.	0.0	
UL (90-100)	0.0	0.0	U0
UH (100-180)	0.0	0.0	U0
TRAPPED LIGHT	0.	0.0	
TOTAL FLUX	6072.	100.0	

BACKLIGHT, UPLIGHT, AND GLARE (BUG) RATINGS
(PER ADDENDUM A FOR IESNA TM-15-11)

BUG RATING: B2 U0 G1



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85360

PAGE: 6 OF 9

ISSUE DATE: 08/12/15

PREPARED FOR: LED ROADWAY LIGHTING LTD.

CANDELA TABULATION

	STREET SIDE										
	0.0	5.0	15.0	25.0	35.0	45.0	55.0	65.0	72.0	75.0	85.0
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	1.	1.	1.	1.	2.	2.	2.	3.	3.	3.
	85.0	5.	6.	8.	7.	7.	8.	8.	10.	57.	59.
V	82.5	19.	19.	27.	24.	18.	22.	21.	50.	415.	439.
E	80.0	38.	39.	54.	39.	36.	45.	44.	154.	1127.	1292.
R	77.5	57.	59.	76.	57.	61.	65.	84.	517.	2017.	2180.
T	75.0	69.	72.	88.	86.	87.	100.	161.	1379.	2707.	2921.
I	72.5	93.	96.	111.	116.	119.	164.	458.	2366.	3623.	3712.
C	70.0	129.	129.	144.	157.	159.	341.	1099.	3185.	4165.	4080.
A	69.0<<	153.	155.	166.	178.	185.	474.	1366.	3450.	4259.	4126.
L	67.5	187.	190.	198.	214.	269.	742.	1748.	3596.	4131.	4080.
	65.0	252.	257.	278.	344.	556.	1252.	2205.	3389.	3602.	3579.
A	62.5	397.	402.	455.	590.	913.	1577.	2331.	3121.	3304.	3262.
N	60.0	601.	616.	666.	823.	1112.	1658.	2280.	2949.	3104.	3061.
G	57.5	769.	775.	819.	949.	1200.	1671.	2232.	2835.	2944.	2903.
L	55.0	877.	883.	921.	1031.	1270.	1675.	2199.	2794.	2876.	2815.
E	52.5	963.	962.	999.	1110.	1342.	1677.	2137.	2578.	2630.	2615.
	50.0	1035.	1032.	1075.	1187.	1409.	1705.	2099.	2412.	2457.	2460.
	47.5	1102.	1098.	1151.	1260.	1476.	1737.	2052.	2285.	2324.	2345.
	45.0	1168.	1174.	1225.	1335.	1536.	1760.	1992.	2161.	2223.	2251.
	42.5	1240.	1243.	1310.	1438.	1609.	1790.	1965.	2063.	2127.	2164.
	40.0	1350.	1349.	1442.	1558.	1684.	1818.	1924.	1974.	2039.	2072.
	37.5	1524.	1519.	1594.	1670.	1751.	1838.	1861.	1901.	1962.	1992.
	35.0	1668.	1673.	1723.	1760.	1803.	1833.	1793.	1836.	1896.	1930.
	30.0	1846.	1843.	1857.	1846.	1812.	1726.	1706.	1766.	1824.	1843.
	25.0	1845.	1839.	1820.	1763.	1688.	1658.	1678.	1732.	1772.	1780.
	20.0	1689.	1683.	1674.	1662.	1660.	1678.	1695.	1732.	1739.	1730.
	15.0	1688.	1686.	1691.	1697.	1704.	1716.	1729.	1735.	1715.	1702.
	10.0	1740.	1736.	1738.	1739.	1744.	1749.	1736.	1716.	1692.	1682.
	5.0	1748.	1743.	1739.	1730.	1722.	1713.	1692.	1678.	1658.	1652.
	0.0	1617.	1617.	1617.	1617.	1617.	1617.	1617.	1617.	1617.	1617.

||
PLANE OF MAXIMUM CANDELA

CONE OF MAXIMUM CANDELA



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955

NVLAP
NVLAP LAB CODE: 200925-0

INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85360
ISSUE DATE: 08/12/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 7 OF 9

CANDELA TABULATION

	HOUSE SIDE	LATERAL ANGLE										
		90.0	95.0	105.0	115.0	125.0	135.0	145.0	155.0	165.0	175.0	180.0
	180.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	175.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	165.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	155.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	145.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	135.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	125.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	115.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	105.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	95.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	92.5	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	90.0	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.	0.
	87.5	3.	3.	3.	3.	3.	2.	1.	0.	0.	0.	0.
	85.0	39.	29.	11.	10.	10.	11.	13.	16.	12.	2.	1.
V	82.5	289.	231.	29.	27.	25.	32.	42.	49.	60.	33.	26.
E	80.0	812.	615.	65.	50.	46.	59.	79.	92.	112.	112.	113.
R	77.5	1479.	1140.	145.	81.	76.	87.	115.	131.	167.	184.	178.
T	75.0	2021.	1611.	290.	118.	110.	113.	142.	154.	204.	225.	222.
I	72.5	2600.	2156.	567.	163.	138.	137.	158.	153.	209.	230.	238.
C	70.0	2953.	2484.	864.	206.	160.	160.	182.	158.	185.	182.	185.
A	69.0<<	3022.	2547.	967.	220.	169.	168.	192.	164.	182.	171.	172.
L	67.5	3064.	2581.	1111.	239.	184.	181.	204.	176.	181.	165.	162.
	65.0	2940.	2538.	1312.	279.	205.	201.	220.	201.	190.	168.	165.
A	62.5	2826.	2522.	1493.	340.	223.	222.	231.	228.	210.	189.	183.
N	60.0	2788.	2550.	1655.	451.	243.	243.	234.	246.	237.	211.	204.
G	57.5	2753.	2576.	1789.	615.	269.	264.	245.	254.	255.	233.	226.
L	55.0	2697.	2551.	1894.	801.	303.	285.	261.	261.	271.	253.	245.
E	52.5	2590.	2457.	1871.	980.	360.	302.	277.	278.	288.	268.	260.
	50.0	2497.	2386.	1883.	1134.	459.	322.	295.	293.	297.	282.	276.
	47.5	2401.	2317.	1882.	1242.	579.	348.	315.	309.	305.	293.	290.
	45.0	2307.	2244.	1862.	1309.	700.	404.	337.	326.	319.	312.	310.
	42.5	2215.	2160.	1834.	1350.	808.	484.	367.	343.	337.	331.	330.
	40.0	2116.	2068.	1790.	1375.	897.	564.	423.	368.	353.	344.	343.
	37.5	2030.	1980.	1743.	1387.	972.	643.	492.	421.	386.	369.	366.
	35.0	1941.	1895.	1693.	1390.	1035.	725.	561.	482.	444.	425.	419.
	30.0	1805.	1757.	1601.	1389.	1141.	907.	731.	629.	569.	540.	533.
	25.0	1701.	1655.	1534.	1396.	1238.	1075.	939.	829.	763.	731.	721.
	20.0	1636.	1598.	1507.	1417.	1323.	1223.	1128.	1055.	998.	973.	962.
	15.0	1614.	1583.	1515.	1452.	1395.	1341.	1289.	1246.	1210.	1195.	1187.
	10.0	1610.	1588.	1544.	1501.	1465.	1435.	1408.	1387.	1372.	1367.	1362.
	5.0	1615.	1603.	1580.	1560.	1541.	1523.	1510.	1502.	1493.	1491.	1487.
	0.0	1617.	1617.	1617.	1617.	1617.	1617.	1617.	1617.	1617.	1617.	1617.

CONE OF MAXIMUM CANDELA



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85360
ISSUE DATE: 08/12/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 8 OF 9

5-DEGREE
ZONAL LUMEN SUMMARY

0- 5	39
5- 10	115
10- 15	185
15- 20	247
20- 25	304
25- 30	361
30- 35	413
35- 40	455
40- 45	491
45- 50	526
50- 55	561
55- 60	583
60- 65	576
65- 70	542
70- 75	405
75- 80	212
80- 85	55
85- 90	3
90- 95	0
95-100	0
100-105	0
105-110	0
110-115	0
115-120	0
120-125	0
125-130	0
130-135	0
135-140	0
140-145	0
145-150	0
150-155	0
155-160	0
160-165	0
165-170	0
170-175	0
175-180	0

10-DEGREE
ZONAL LUMEN SUMMARY

0- 10	153
0- 20	585
0- 30	1250
0- 40	2118
0- 50	3135
0- 60	4279
0- 70	5397
0- 80	6014
0- 90	6072
0-100	6072
0-110	6072
0-120	6072
0-130	6072
0-140	6072
0-150	6072
0-160	6072
0-170	6072
0-180	6072



itl boulder
THE LIGHT CENTER OF THE INDUSTRY SINCE 1955



INDEPENDENT TESTING LABORATORIES, INC.
4066 CAMELOT CIRCLE, LONGMONT, CO 80504 USA

PHONE: (303) 442-1255 • FAX: (970) 535-3114 • E-MAIL: itl@itlboulder.com • WEBSITE: www.itlboulder.com

REPORT NUMBER: ITL85360
ISSUE DATE: 08/12/15
PREPARED FOR: LED ROADWAY LIGHTING LTD.

PAGE: 9 OF 9

ADDRESS: 115 CHAIN LAKE DRIVE
SUITE 201
HALIFAX, NOVA SCOTIA, CANADA B3S1B3

THIS ITL REPORT WITH THE USE OF THE NVLAP LOGO SHALL NOT BE USED BY
THE CLIENT TO CLAIM PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT
BY NVLAP, NIST, OR ANY AGENCY OF THE FEDERAL GOVERNMENT.